


PRODUCT SPECIFICATIONS

General	Model	1			CPCD20
	Power Type	2			Diesel
	Load Capacity	3		kg	2000
Weights	Load Center Distance	4	@ rated load center	mm	500
	Service Weight	5	unloaded	kg	3370
	Axle Load	6	loaded,front/rear	kg	4390/670
Tires		7	unloaded,front/ rear	kg	1350/2020
	Tire Type	8			Pneumatic
	Wheels	9	front / rear		2/ 2
Mast	Wheelbase	10		mm	1650
	Tire Size	11	front		7.00-12-12PR
		12	rear		6.00-9-10PR
Mast	Tread Width	13	front/rear	mm	960/970
	Max. Fork Height	14	with std 2-stage mast	mm	3000
	Free Lift	15	with std 2-stage mast	mm	140
Chassis	Height, Upright Lowered	16	with std 2-stage mast	mm	2070
	Height, Upright Extended	17	with std 2-stage mast	mm	4025
	Mast Tilt, Fwd/Back	18	with std 2-stage mast	deg	6° / 12°
Performance	Fork Carriage	19	width	mm	1040
	Fork Spread	20	minimum/maximum	mm	272/1072
	Fork Dimension	21	T x W x L	mm	40 x 122 x 1070
Systems	Length to Fork Face	22	with std 2-stage mast	mm	2500
	Overall Width	23		mm	1150
	Overhead Guard Height	24		mm	2100
Internal combustion	Turning Radius	25	minimum outside	mm	2190
	Fork Overhang	26	with std 2-stage mast	mm	476
	Min.Right Angle Stacking Aisle Width	27	add load length and clearance	mm	3935
Performance	Ground Clearance	28	loaded below mast	mm	110
		29	center of wheelbase	mm	120
	Travel Speed	30	loaded/unloaded	km/h	19/ 20
Systems	Lift Speed	31	loaded/unloaded	mm/s	530/550
	Lowering Speed	32	loaded/unloaded	mm/s	420/510
	Max. Drawbar Pull	33	loaded	N	16475
Internal combustion	Max. Gradeability	34	loaded/unloaded	%	18/ 20
	Brakes	35	service		Foot/Hyd
		36	parking		Hand /Mech
Internal combustion	Engine	37	manufacturer		Yanmar
		38	model		4TNE92-HRJ
		39	emission compliance		EU III
Internal combustion		40	cylinders		4
		41	displacement	L	2.659
		42	rated power	kW/rpm	32.8/2450
Internal combustion		43	max. torque	N.m/rpm	140/1700





E SERIES



Engine	Yanmar
Fuel	Diesel
Rated load	2000kg
Rated Power	32.8 kW

CPCD20

***E SERIES INTERNAL COMBUSTION
COUNTERBALANCED FORKLIFT***

TOUGH WORLD. TOUGH EQUIPMENT.