



Engine	Kubota
Power Type	Diesel
Base Capacity	2500 kg
Rated Power	42.6kW

CLG2025H-RT4
**FOUR-WHEEL DRIVE ROUGH
TERRAIN FORKLIFT**

SPECIFICATION

General	Model	1			CLG2025H-RT4	
	Power Type	2			Diesel	
	Base Capacity	3		kg	2500	
	Load Center	4	@ rated load center	mm	500	
Weights	Service Weight	5	unloaded	kg	4900	
	Axle Load	6	loaded/unloaded, front	kg	6220/2150	
		7	loaded/unloaded, rear	kg	1180/2750	
Tires	Tire Type	8			Pneumatic	
	Wheels	9	front / rear		2x/2x	
	Wheelbase	10		mm	1880	
		11	front		14-17.5-14PR	
	Tire Size	12	rear		10.0-16.5-10PR	
		13	front/rear	mm	1250/1220	
Mast	Max. Fork Height	14	with std 2-stage mast	mm	3000	
	Freelift	15	with std 2-stage mast	mm	100	
	Height, Upright Lowered	16	with std 2-stage mast	mm	2355	
	Height, Upright Extended	17	with std 2-stage mast	mm	4310	
	Mast Tilt, Fwd/Back	18	with std 2-stage mast	deg	10/12	
	Carriage	19	width	mm	1200	
	Fork Spread	20	minimum/maximum	mm	260-1200	
	Fork Dimension	21	T x W x L	mm	122 x 50 x 1070	
	Length to Fork Face	22	with std 2-stage mast	mm	3100	
	Overall Width	23		mm	1600	
Chassis	Overhead Guard Height	24		mm	2410	
	Turning Radius	25	minimum outside	mm	3300	
	Fork Overhang	26	with std 2-stage mast	mm	590	
	Min.right angle stacking aisle width	27	add load length and clearance	mm	5305	
		28	loaded below mast	mm	270	
	Ground Clearance	29	center of wheelbase	mm	265	
		30	loaded/unloaded	km/h	20/20	
	Performance	Lift Speed	31	loaded/unloaded	mm/s	500/520
Lower Speed		32	loaded/unloaded	mm/s	500/500	
Max. Drawbar Pull		33	loaded	kg	38.8	
Max. Gradeability		34	loaded/unloaded	%	46	
System		Brakes	35	service		Foot/Hyd
	36		Parking		Hand/Mech	
Internal Combustion	Engine	37	manufacturer		Kubota	
		38	model		V2403-CR-TE5B	
		39	emission compliance		EU Stage V	
		40	cylinders		4	
		41	displacement	L		2.434
		42	rated power	kW/rpm		42.6/2400
		43	max. torque	N.m/rpm		197/1500

