

<b>Engine</b>	Cummins 4BTAA3.9-C110
<b>Rated Power</b>	82 kW (110 hp / 111 ps) @ 2,200 rpm
<b>Nominal Amplitude Range</b>	0.6 / 0.35 mm
<b>Vibration Frequency Range</b>	50 / 67 Hz
<b>Centrifugal Force Range</b>	79 / 68 kN
<b>Working Width</b>	1,600 mm
<b>Operating Weight</b>	8,000 kg

# CLG6208E ROLLER

# CLG6208E SPECIFICATIONS >>>

## ENGINE

Emission Regulation	Tier 2 / Stage II
Manufacturer	Cummins
Model	4BTAA3.9-C110
Rated Power	82 kW (110 hp / 111 ps) @ 2,200 rpm
Peak Torque	500 N·m
Number of Cylinders	4
Aspiration	Turbocharged
Cooling Type	Water

## ELECTRICAL SYSTEM

System Voltage	24 V
----------------	------

## DRIVE TRAIN

Theoretical Gradeability	35%
Transmission Type	Hydrostatic
1st Max. Travel Speed, Fwd	4.5 km/h
2nd Max. Travel Speed, Fwd	6.4 km/h
3rd Max. Travel Speed, Fwd	12 km/h
Outside Turning Radius	6,000 mm

## AXLES

Steering System	Hydraulic
Steering Method	Oscillating and Articulated
Steering Angle	± 35°
Steering Relief Pressure	16 Mpa

## BRAKES

Service Brake Type	Hydrostatic
Service Brake Actuation	Hydraulic
Parking Brake Actuation	Auto brake

## DIMENSIONS

A Overall Length	4,600 mm
B Overall Width	1,740 mm
C Drum Width	1,600 mm
D Drum Diameter	1,150 mm
E Drum Thickness	15 mm
F Wheelbase	3,250 mm
G Min. Ground Clearance	280 mm
H Overall Height	3,050 mm

## HYDRAULIC SYSTEM

Main Pump Type	Piston pump
Main Relief Pressure	34.5 Mpa

## PERFORMANCE

Front Drum Static Linear Load	250 N/cm
Rear Drum Static Linear Load	250 N/cm
Number of Vibrating Drums	2
Nominal Amplitude Range	0.6 / 0.35 mm
Vibration Frequency Range	50 / 67 Hz
Centrifugal Force Range	79 / 68 kN
Number of Amplitude Settings	2

## OPERATING WEIGHTS

Operating Weight	8,000 kg
Weight on Front Drum	4,000 kg
Weight on Rear Drum	4,000 kg

## SERVICE CAPACITIES

Fuel Tank	100 L
Engine Oil	11.5 L
Hydraulic Oil Tank	60 L
Cooling System	20 L
Water Tank	500 L

